



Specifications Ledvance LED  
Floodlight Flex White 80W 8400lm  
55x120D - 822 Extra Warm White |  
IP66 - Dali Dimmable - Asymmetrical

[View Product](#)

General Information

|                          |                                                              |
|--------------------------|--------------------------------------------------------------|
| SKU                      | 252323                                                       |
| EAN                      | 4099854374142                                                |
| Brand                    | Ledvance                                                     |
| Manufacturer Name        | FLOODLIGHT FLEX DALI ASYMMETRIC 55 X 120 80W 822 A55X120 WAL |
| Any Lamp all-in warranty | 5 Years                                                      |
| Average Lifetime (h)     | 120000                                                       |

Technical Information

|                             |                       |
|-----------------------------|-----------------------|
| Technology                  | LED Integrated        |
| Wattage                     | 80                    |
| Replaces (Watt)             | 70                    |
| Voltage (V)                 | 220-240               |
| Dimmable                    | Dimmable with Dali    |
| Colour Code                 | 822 Extra Warm White  |
| Colour temperature (Kelvin) | 2200 Extra Warm White |
| Colour Rendering (Ra)       | 80-89                 |
| Colour of Light             | White                 |
| Light colour options        | Single Color          |
| Luminous Flux (Lumen)       | 8400                  |
| Luminous Efficacy (lm/W)    | 105                   |

|                       |                |
|-----------------------|----------------|
| Beam Angle (degree)   | 55x120         |
| Power factor          | >0.90          |
| Product Type Category | LED Floodlight |

## Fixture Information

|                        |                    |
|------------------------|--------------------|
| Mounting Method        | Surface            |
| Fixture Connection     | Screwless terminal |
| Light Distribution     | Asymmetrical       |
| IP-rating              | IP66               |
| Impact Protection (IK) | IK08 - 5 joules    |
| Operating Temperature  | -30 to +50         |
| Colour of the Fixture  | White              |
| Housing                | Aluminium          |
| Colour of material     | White              |
| Emergency Lighting     | No Emergency Unit  |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 479 |
| Width (mm)  | 304 |
| Height (mm) | 67  |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process